



## ГОФРА ПОВІТРЯНА | SPIRAL HOSE GRAY



- Гофрований спіральний армований шланг, виготовлений з еластичного ПВХ, армування вироблено міцним та жорстким спіральним прутом із ПВХ. Шланг використовується для відсмоктування повітря, диму, газів, в установках кондиціонування та вентиляції, для транспортування сипучих матеріалів, для зрошення, зливу та перекачування мінеральних добрив. Залежно від сфери застосування шланг має властивість згинатися і приймати будь-яку форму. Стійкі до тиску та зовнішніх ударів. Пакування поліетиленова плівка.
- Corrugated spiral reinforced hose made of flexible PVC, the reinforcement is made of strong and rigid PVC spiral rod. The hose is used for suction of air, smoke, gases, in air conditioning and ventilation installations, for transporting bulk materials, for irrigation, draining and pumping of mineral fertilizers. Depending on the field of application, the hose has the ability to bend and take any shape. Resistant to pressure and external shocks. Packaging polyethylene film.

### SPIRAL HOSE "GRAY"

Маркування | Marking: SPIRAL HOSE "GRAY" - MADE IN UKRAINE

Діаметр Inches [inc]	Ø Внутрішній [мм] Ø internal [mm]	Робочий тиск Working pressure [bar]	Габарити бухти, ДхШхВ мм	Довжина бухти [м] Length [m]	Вага бухти, кг Bay weight, kg	Ціна (USD\$)
1 1/2"	38	3	700x700x220	25	6,5	40,95
2"	50	3	760x760x260	25	9,5	65,62
2 1/2"	63	3	210x1050x1050	25	13,5	87,15
3"	75	3	240x1100x1100	25	18	98,17
4"	100	3	450x1250x1250	25	28	147,26

- Максимальний тиск 5 bar Робоча температура -5/+60°C Довжина 25, 50м
- Maximum pressure 5 bar Operating temperature -5/+60°C Length 25, 50 m

- Гарантія 3 роки за дотримання умов експлуатації
- 3 years warranty for compliance with operating conditions